



Demolition Grapples

General Specifications for XCG2 Series Grapples

Excavator Weight [x1000lbs]	Model	Tine Config.	Capacity m ³ [yd ³]	Weight kg [lbs]	Moving Jaw Width mm ["]	Fixed Jaw Width mm ["]	Max. Opening mm ["]	Min. Opening mm ["]	Height mm ["]
09 – 14 t [20-31]	12CG25	2/3	0.5 [0.6]	864 [1900]	540 [21]	910 [36]	1,651 [65]	280 [11]	1,231 [49]
	12CG27	3/4	0.6 [0.8]	1,050 [2314]	783 [31]	1,102 [43]			
13 – 17 t [29-37]	15CG25	2/3	0.8 [1.0]	907 [2000]	580 [23]	980 [39]	1,713 [67]	322 [13]	1,402 [55]
	15CG27	3/4	1.0 [1.3]	1,111 [2450]	855 [34]	1,205 [47]			
16 – 24 t [35-53]	20CG25	2/3	1.5 [2.0]	1,318 [2900]	650 [26]	1,100 [43]	2,476 [97]	357 [14]	1,551 [61]
	20CG27	3/4	1.8 [2.4]	1,500 [3300]	900 [35]	1,270 [50]			
	20CG29	4/5	2.1 [2.8]	1,727 [3800]	1,165 [45]	1,505 [59]			
22 – 28 t [48-62]	25CG25	2/3	2.1 [2.8]	1,640 [3615]	690 [27]	1,170 [46]	2,721 [107]	379 [15]	1,671 [66]
	25CG27	3/4	2.7 [3.5]	1,864 [4100]	970 [38]	1,370 [54]			
	25CG29	4/5	3.0 [3.9]	2,050 [4518]	1,230 [48]	1,590 [62]			
26 – 38 t [57-84]	30CG25	2/3	2.8 [3.7]	1,905 [4200]	746 [29]	1,268 [50]	2,881 [113]	413 [16]	1,645 [65]
	30CG27	3/4	3.1 [4.0]	2,177 [4800]	1,124 [44]	1,587 [62]			
	30CG29	4/5	3.3 [4.3]	2,782 [6120]	1,305 [51]	1,688 [66]			
35 – 50 t [77-110]	40CG25	2/3	3.4 [4.5]	2,900 [6392]	846 [33]	1,436 [56]	3,071 [121]	460 [18]	1,994 [78]
	40CG27	3/4	4.1 [5.3]	3,045 [6700]	1,271 [50]	1,796 [70]			
	40CG29	4/5	4.7 [6.2]	3,200 [7053]	1,568 [62]	2,028 [80]			
48 – 60 t [106-132]	55CG25	2/3	4.3 [5.6]	3,600 [7936]	914 [36]	1,552 [61]	3,100 [122]	480 [19]	2,130 [84]
	55CG27	3/4	4.8 [6.3]	3,950 [8708]	1,382 [54]	1,951 [77]			
59 – 90 t [130-198]	70CG25	2/3	5.0 [6.5]	4,849 [10690]	982 [39]	1,667 [66]	3,347 [132]	526 [21]	2,314 [91]
	70CG27	3/4	5.7 [7.5]	5,121 [11290]	1,492 [59]	2,106 [83]			
89 – 125 t [196-276]	100CG25	2/3	6.0 [7.8]	5,500 [12125]	1,031 [41]	1,770 [70]	4,424 [174]	624 [25]	2,685 [105]
	100CG27	3/4	6.4 [8.4]	5,712 [12593]	1,575 [62]	2,314 [91]			

Option Codes:

- U** - QAU (Pin-Grabber) compatible. Works with or without a pin grabber type coupler.
- Q** - Quick Coupled. Works with Nye Stealth or customer's choice of Quick Coupler.
(Couplers are sold separately)