



Concrete Pulverizer

General Specifications for XCP3 Series

Excavator Weight [x1000lbs]	Model	Jaw Config.	Weight Kg [lbs]	Moving Jaw Width mm ["]	Fixed Jaw Width mm ["]	Max. Opening mm ["]	Jaw Depth mm ["]	Height mm ["]
09 – 14 t [20-31]	12CP37	3/4	885 [1,950]	397 [15.5]	539 [21]	533 [21]	406 [16]	673 [26]
13 – 17 t [29-37]	15CP37	3/4	997 [2,200]	416 [16]	620 [24]	660 [26]	457 [18]	786 [31]
16 – 24 t [35-53]	20CP37	3/4	1,088 [2,400]	471 [19]	680 [27]	792 [30]	522 [21]	863 [34]
	20CP39	4/5	1,270 [2,800]	471 [19]	680 [27]			
22 – 28 t [48-62]	25CP37	3/4	1,424 [3,140]	547 [21]	783 [31]	889 [35]	600 [24]	973 [38]
	25CP39	4/5	1,542 [3,400]	565 [22]	783 [31]			
26 – 38 t [57-84]	30CP37	3/4	1,878 [4,140]	568 [22]	827 [32.5]	1016 [40]	681 [27]	1117 [44]
	30CP39	4/5	1,950 [4,300]	605 [24]	840 [33]			
35 – 50 t [77-110]	40CP37	3/4	2,663 [5,870]	642 [25]	920 [36]	1168 [46]	776 [31]	1286 [49]
	40CP39	4/5	2,812 [6,200]	678 [27]	939 [37]			
48-60 t [106-132]	55CP39	4/5	4,350 [9,590]	760 [30]	1050 [41]	1250 [49]	872 [34]	1439 [57]
59 – 90 t [130-198]	70CP39	4/5	5,550 [12,175]	829 [33]	1111 [44]	1321 [52]	939 [37]	1514 [60]
89 -125 t [196-276]	100CP39	4/5	6,680 [14,675]	862 [34]	1180 [46]	1473 [58]	1054 [42]	1704 [67]

Option Codes:

U - QAU (Pin-Grabber) compatible. Works with or without a pin grabber type coupler.

Q - Quick Coupled. Works with Nye Stealth or customer's choice of Quick Coupler. (Couplers sold separately)

D - Ripper Option. Pulverizer is equipped with a 4 position ripping shank.

3585 Mavis Rd. Mississauga, ON Canada L5C 1T7 T: 905 897 2311 F: 905 897 2312

sales@nye.ca

nye.ca